Each

Tuesday, 8/22/2006 9:59:58 AM Jean-Luc Menard **Process Sheet** : FUEL PURGE CANISTER **Drawing Name** : CU-DAR001 Dart Helicopters Services Customer Job Number : 28225B : 10442 **Estimate Number** : D32623 **Part Number** P.O. Number **Drawing Number** D3262 REV B S.O. No. : : 8/22/2006 This Issue : N/A - NC **Project Number** Prsht Rev. MACHINED PARTS ":¹8/17/2006 Type **Drawing Revision** First Issue Material : 26761B **Previous Run** : 9/10/2006 Qty: 16 Um: **Due Date** Written By Checked & Approved By Removed P/O for liquid penetrant inspection K Comment J/JLM **Additional Product** Job Number: Description: Seq. #: **Machine Or Operation:** 6061-T6 Bar .50" x 6.0" M6061T6B0500X06000 1.0 Total: 15.4694 f(s) Comment: Qtv.: 0.9668 f(s)/Unit Material: 6061-T6/T651 (QQ-A-200/8 or 225/8) 0.500" thick (M6061T6B0.500x06.000) Identify for D3262-3 Batch: M101422 BAND SAW BAND SAW 2.0 Comment: BAND SAW Cut blanks: 6.000" x 0.500" x 5.400" long Bar HAAS CNC VERTICAL MACHINING # 3.0 HAAS1 Comment: HAAS CNC VERTICAL MACHINING #1 Machine as per Folio FA457 and Dwg D3262 Identify for D3262-3 Deburr

SECOND CHECK

4.0

5.0

QC2

QC8


Comment: SECOND CHECK


Comment: INSPECT PARTS AS THEY COME OFF MACHINE

Tuesday, 8/22/2006 9:59:58 AM Date: Jean-Luc Menard User: **Process Sheet Drawing Name: FUEL PURGE CANISTER** Customer: CU-DAR001 Dart Helicopters Services Part Number: D32623 Job Number: 28225B Job Number: Description: Seq. #: **Machine Or Operation:** PACKAGING RESOURCE #1 6.0 PACKAGING 1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location: DOCUMENT CONTROL 7.0 Comment: DOCUMENT CONTROL 06/08/28 Inspection Level 21 h 6.06.29 Job Completion




DESIGN DRAWN BY			DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA				
CHEC	KED MI	APPROVED:	DRAWING NO	REV. B			
	#	#	D3262 SHEET	OF 2			
DATE			TITLE	SCALE			
05.0	02.14		FUEL PURGE CANISTER	1:1			
 Α		04.05.06	NEW ISSUE				
В	•	05.02.14	ADD PRESSURE TESTING OPTION				





D3262-041 CANISTER ASSEMBLY



D3262-041:

- 1) MATERIAL: 6061-T6 (WW-T-700/6 OR QQ-A-200/8 OR QQ-A-225/8) TUBING 5.00 OD x 0.125 WALL (6061T6T5.000W.125) ·
- 2) WELD PER QSI 004.
 3) LIQUID PENETRANT INSPECT PER ASTM E1417 LEVEL 1 OR PRESSURIZE TO 10 psi AND SUBMERGE UNDER WATER TO CHECK FOR LEAKS
- 4) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- POWDER COAT ASSEMBLY WHITE (4.3.5.1) PER DART QSI 005 4.3 5) BREAK ALL SHARP EDGES 0.005 TO 0.010


- 6) ALL DIMENSIONS ARE IN INCHES
 7) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
 8) IDENTIFY WITH DART P/N & B/N USING FINE POINT PERMANENT INK MARKER


Copyright © 2004 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.



DESIGN	DRAWN BY	DART AEROSPAC HAWKESBURY, ONTARIO, C	
CHECKED	APPROVED.	DRAWING NO.	REV. B
1 #	#	D3262	SHEET 2 OF 2
DATE		TITLE	SCALE
05.02.14		FUEL PURGE CANISTER	1:3





D3262-3

- 1) MATERIAL: 6061-T6/T651 (QQ-A-200/8 OR QQ-A-225/8) BAR (REF. DART SPEC. M6061T6B)
- 2) TAP HOLE 9/16-18 UNF-3B PER MIL-S-8879
- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.010
- 6) PART IS SYMMETRIC ABOUT CENTERLINE
- 7) ENGRAVE DART LOGO AS SHOWN USING 0.75 HIGH x 0.010 DEEP (MAX) LETTERS WITH (MIN) TOOL RADIUS OF 0:25

Copyright @ 2004 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

DART AEROSPACE LTD	Work Order: 78723 B		
Description: Cap	Part Number:	D3262-3	
Inspection Dwg: D3262 Rev: B		Page 1 of 1	

FIRST ARTICLE INSPECTION CHECKLIST

X First Article Prototype

Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments
0.070 x 45°	+/-0.010	0.067X45)			
0.45	+/-0.030	0.440				
R0.063	+/-0.010	R0.063				
0.090	+/-0.010	0.087				
0.33	+/-0.030	0.335	-			
5.005	+0.010/-0.000	5.000				
0.688	+0.015/-0.000	0.688				
3.250	+/-0.005	3.252			^	
0.875	+/-0.010	0.870	_			
Ø0.516	+0.005/-0.000	80.578				
Ø5.190	+/-0.010	05.188				
0.083	+0.015/-0.000	0.090				
Ø0.580	+0.005/-0.000	00.581	\			•
Ø5.005	+0.010/-0.000	05.010				
,						
	-					

Measured by:	and	Audited by:	Prototype Approval:	N/A
Date:	01/08/21	Date: 06/08/6	Date:	N/A

Rev	Date	Change			Revised by	Approved
A	04.09.03	New Issue	P/O D3262-041		KJ/JLM	
В	05.04.28	Dimensions and tolerances revised			KJ/JLM	